



Coir Logs

High Density | 100% Biodegradable

Available Sizes: (1.5m x 200mm)
(3m x 200mm)
(3m x 300mm)



Product Features

- ✓ 100% biodegradable.
- ✓ High density fibres for increased performance and life span.
- ✓ 2 - 3 year life-span.
- ✓ Easy installation.

**Pre-drilled peg holes
for fast and easy
installation**



Aussie Environmental Coir Logs are lightweight and easy to install. Ideal for constructing check structures, establishing vegetation, managing changes in stream flow velocity, shaping channels & stabilising shorelines. Made from densely packed coconut fibre wrapped with coir netting. Coir Logs are 100% biodegradable and blend into their surroundings over time. Coir Logs are flexible and can curve around river banks and existing vegetation. Coir Logs can be used in open drains to slow water velocity and capture sediments or be used in streams and rivers to produce a natural wall of protection for plants and soil.

Ph: 07 5315 5431

info@aussieenvironmental.com.au

aussieenvironmental.com.au

19 Central Park Drive
Yandina, Queensland 4561

Coir Logs

With Pre-drilled Installation Holes



Applications

- River bank stabilisation.
- Wetland erosion.
- Building sites.
- Wall protection for plants & soil.
- Dam construction.
- Minimise wave action.
- Pipeline construction.
- Swale drains.
- Embankments.

Specifications:

Name: Coir Log
Material: High Density Coconut Coir Fibres
Life Span: Biodegrades after 2-3 years

Length	Diameter	Weight	Longevity
1.5m	200mm	8 Kgs	24 months
3m	200mm	15 Kgs	24 months
3m	300mm	25 Kgs	24 months

How to Install Coir Logs

For Drain and Slope Installation

- For maximum stability create a trench 100mm deep.
- Place log into the trench and pack loose soil back around the log.
- Use only untreated hardwood timber pegs 600 or 900mm high.
- Insert pegs through each pre-drilled hole.
- Pegs should be at least 200 mm into the ground.
- Maintenance should always be carried out; this may include re-staking and disposal of excess sediments.



Coir Logs with pre-drilled holes™
for easy installation



Ph: 07 5315 5431

info@aussieenvironmental.com.au

aussieenvironmental.com.au

19 Central Park Drive
Yandina, Queensland 4561